



## Traffic Light (TL)

### Specifications

<b>Make</b>	<b>KENT ITS</b>
<b>Model</b>	Kent/TL_V1.1
<b>Technology</b>	LED
<b>Dimension</b>	280mm x 560mm x 350mm
<b>Material and finishes</b>	Polypropylene / Polycarbonate /Mild Steel with black color powder coated with Sun visor
<b>Aspect diameter</b>	200mm
<b>Aspect Color</b>	RED and Pure Green
<b>Interface</b>	Directly 230V/Ac switching from potential free devices
<b>Visibility</b>	>20 mtrs
<b>Cables</b>	Power Cable
<b>LED Type</b>	Super Bright Day visible 8000 - 10000 mcd at 20 mA, 45° viewing angle for Red 8000 - 10000 mcd at 20 mA, 45° viewing angle for GREEN
<b>Weight</b>	<6 Kg
<b>Operating Voltage</b>	220-270VAc /50-60 Hz
<b>Power Consumption</b>	10W max
<b>Installation</b>	Bolting Arrangement to Pole
<b>Environment Conditions</b>	Operating Temp : -10°C to 60°C Humidity : 0 to 90%
<b>Reliability</b>	MTBF: 100,000 hours MTTR: 0.20 hrs
<b>Access For maintenance</b>	Front Door Access for Easy Maintenance
<b>Protection</b>	IP 65
<b>Certification</b>	CE – EN Certified